

cuprotec® – Wall heating element type S, copper ribbed tube, di16 mm, do 39 mm, with stand consoles made of synthetic material (1 piece per meter), with copper soldering Cu 16/15 x 1 mm.

Supply and mount.

Installation height: 95mm

Installation depth: 57 bzw. 84mm

Lengths: 75 – 400cm (in 25 cm–Sprüngen)

Installation type 1: for the application with plasterboards

Installation type 2: for the application as border skirting

(select one!)

Shaft skirting/facing: A: custom-made skirting

B: Thermo skirting

Inlet / Outlet: °C, ø = 15mm

.....m cuprotec® – wall heating element as described above, as a starting element with thermostat drag in axial form (Fabr. OVENTROP, type AV DN 15 1/2 ") for the connection of the remote control, incl. return flow curves, fittings and connections. Supply and mount.

Material price:EUR/m

Wage:EUR/m

Total:**EUR/m**

.....EUR

.....piece Cut charge for the above positions.

Material price:EUR/piece

Wage:EUR/piece

Total:**EUR/piece**

.....EUR

..... m cuprotec® – wall heating element as described above, as a connecting element with inlet- and return flow connections. Supply and mount.

Material price:EUR/m

Wage:EUR/m

Total:**EUR/m**

.....EUR